

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/EP05/002080

International filing date: 28 February 2005 (28.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0405493.8  
Filing date: 12 March 2004 (12.03.2004)

Date of receipt at the International Bureau: 31 March 2005 (31.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/EP200 5 / 0 0 2 0 8 0



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ


28. 02. 2005

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

*William Morell*

Dated 10 January 2005



Patents Form 1/77

Patents Act 1977  
(Rule 16)

12MAR04 E880214-1 D00866

P01/7700 0.00-0405493.8 ACCOUNT CHA

1/77

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

|    |   |   |   |                                    |
|----|---|---|---|------------------------------------|
| 1. | Your reference  | GB  | Case  | WW/3-22354/P1                      |
| 2. | Patent application number<br>(The Patent Office will fill in this part)   | 12 MAR 2004   |   | 0405493.8                          |
| 3. | Full name, address and postcode of the<br>or of each applicant<br>(underline all surnames)  | <b>Ciba Specialty Chemicals Water Treatments Limited</b><br><b>Cleckheaton Road</b><br><b>Low Moor</b><br><b>Bradford</b><br><b>West Yorkshire</b><br><b>BD12 0JZ</b> |   |                                    |
|    | Patent ADP number (if you know it)  | 07585391005   |   |                                    |
|    | If the applicant is a corporate body, give<br>the country/state of its incorporation  | England   |   |                                    |
| 4. | Title of invention  | Dewatering Process  |   |                                    |
| 5. | Name of your agent (if you have one)  | Ciba Specialty Chemicals Water Treatments Limited   |   |                                    |
|    | "Address for service" in the United<br>Kingdom to which all correspondence<br>should be sent<br>(including the postcode)  | <b>Patents Department</b><br><b>PO Box 38</b><br><b>Cleckheaton Road</b><br><b>Low Moor</b><br><b>Bradford</b><br><b>West Yorkshire</b><br><b>BD12 0JZ</b>            |   |                                    |
|    | Patents ADP number (if you know it)   | 07585391002 ✓   |   |                                    |
| 6. | If you are declaring priority from one<br>or more earlier patent applications,<br>give<br>the country and the date of filing of the<br>or of each of these earlier applications<br>and (if you know it) the or each<br>application number   | Country   | Priority application number<br>(if you know it) | Date of filing<br>(day/month/year) |
| 7. | If this application is divided or<br>otherwise derived from an earlier UK<br>application, give the number and the<br>filing date of the earlier application   | Number of earlier<br>application  |   | Date of filing<br>(day/month/year) |
| 8. | Is a statement of inventorship and of<br>right to grant of a patent required in<br>support of this request? (Answer 'Yes' if:<br>a) any applicant named in part 3 is not an<br>inventor, or<br>b) there is an inventor who is not named as<br>an applicant, or<br>c) any named applicant is a corporate body.<br>(see note (d)) | YES   |   |                                    |

Patents Form 1/77

0097442 12-Mar-04 09:55

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form -

Description 17

Claim(s) 2 

Abstract 1


Drawing(s)

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) 1 

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application

Signature

Date



12 March 2004

12.

Name and daytime telephone number of person to contact in the United Kingdom

Jane Spinks

01274 417558

## Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

## Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) Once you have filled in the form you must remember to sign and date it.
- e) For details of the fees and ways to pay please contact the Patent Office.

Patents Form 1/77

0097442 12-MAR-04 09:55

WW/3-22354/P1

1

DUPLICATE

Dewatering Process

The present invention concerns the flocculation and dewatering of aqueous suspensions to form a dewatered cake.

5

It is well known to apply flocculants to aqueous suspensions in order to separate solids from the suspension. For instance it is common practice to flocculate and then dewater suspensions containing either suspended solid, organic material or mineral solids. For instance it is common practice to flocculate sludges such as sewage sludge, waste waters, textile industry effluents, red mud from the Bayer Alumina process and suspensions of coal tailings etc. Flocculation is usually achieved by mixing into the suspension the flocculant, allowing the suspended particles to flocculate and then dewatering the flocculated suspension to form a dewatered cake.

15

In the dewatering of suspensions it is known to add a high molecular weight, water soluble polymer as a flocculant to the suspension in order to remove the liquid from the suspension and greatly increase the dry solids of the suspension. High molecular weight flocculants may be cationic, anionic, nonionic or amphoteric in nature. The choice of polymeric flocculant will largely depend upon the substrate which is being treated. For instance it is common practice to use high molecular weight cationic flocculants to treat aqueous suspensions comprising suspended organic material, for instance sewage sludge. In paper-making it is known to use either cationic, nonionic, anionic or amphoteric flocculants. Flocculation of mineral suspensions is frequently effected by use of anionic flocculants.

20

25

It is standard practice to apply polymers as aqueous compositions to flocculate suspensions containing suspended organic material. Generally the compositions of polymers are relatively dilute, for instance no more than 1% and usually no more than 0.5%, and can be as low as 0.2% by weight or lower.

30

Various alternative methods of introducing a flocculant into a suspension have been proposed. WO-A-02/079099 describes a method in which at least one flocculant emulsion is added directly to a solids liquid separation process and  
5 inverted in situ such that flocculant is released directly into the application. The emulsion is added specifically at the solids liquid separation process and subjected to an effective amount of high shear for sufficient time and pressure to ensure rapid inversion of the emulsion and complete release of the flocculant into the bulk suspension before any initial separation .

10 WO-A-98/31749 and WO-A-98/31748 are both concerned with preparing dispersions of high intrinsic viscosity cationic polymers in an aqueous and medium containing dissolved low intrinsic viscosity cationic polymer. The product thus formed is an aqueous dispersion of undissolved high intrinsic  
15 viscosity cationic polymer, which is a convenient way of providing high molecular weight flocculants. The dispersion polymer can be dissolved in water to a conventional concentration or can be added directly to a suspension.

It is also known to use two different polymeric flocculants in the same process.

20 In commercial practice the dewatering of sewage sludge may involve the addition of two polymeric flocculants which have the same charge (co-ionic). In other processes it is known to apply two polymers of opposite charge (counter-ionic). Where two polymeric flocculants are applied to an aqueous suspension they may be added simultaneously or more usually sequentially.

25 WO-A-01/05712 reveals a process of dewatering a suspension by adding to the suspension a concentrated and a dilute solution of polymeric flocculants substantially simultaneously. Both the concentrated and diluted solutions of polymer are added at conventional concentrations of no more than 1% and  
30 usually much less than this.

WO-A-02/72482 describes a process of flocculating and dewatering an aqueous suspension of suspended solids in which a polymer composition comprising 40% and 60% by weight polymer and a polymer composition comprising between 0.05 and 0.2% by weight polymer are introduced simultaneously.

- 5 Although the process brings about some improvements in filtration and free drainage, it would be desirable to improve upon the cake solids obtained in dewatering suspensions, especially for sewage sludges.

- 10 International application PCT/EP03/09381 unpublished at the date of filing describes a method of dewatering a suspension employing a composition comprising a cationic polymer flocculant and a coagulant in which the coagulant is encapsulated. After free drainage of the suspension the coagulant is released into the suspension for example by rupturing of the capsules that enclose the coagulant or by migration from a matrix in which the coagulant is
- 15 entrapped. Although significant improvements in cake solids can be obtained it would be desirable to provide equivalent or improved cake solids using flocculant products that can be more easily manufactured and/or applied.

- 20 However, achieving high cake solids can sometimes be difficult, particularly in the dewatering of sewage sludges. It is also known to add a flocculant or coagulant to assist the initial dewatering of a suspension followed by further addition of flocculant or coagulant and then further dewatering to achieve high cake solids. Such processes are described in JP-A-10-249398, JP-A-61-257300, JP-A-06-343999, JP-A-06-344000 and EP-A-1035077.

- 25 JP10249398 describes a two-stage dewatering process in which a polyamidine-base high molecular flocculant is used as either the first or second high molecular flocculants in the two-stage dehydration method. The polyamidine-base high molecular flocculant is obtained by copolymerizing (meth)acrylonitrile
- 30 or N-vinylcarboxylic acid amide, N-isopropenylcarboxylic acid amide, N-

vinylcarboxylic acid imide or N-isopropenylcarboxylic acid imide and hydrolyzing the copolymer to the amidine.

- 5 JP61257300 is concerned with reducing water content in dehydrated sludge cakes. Sewage sludge is dehydrated in a dehydrator after adding an organic high molecular flocculant to the sludge and then dehydrated further in the dehydrator by adding an inorganic treatment agent such as ferric chloride and then separating liquid from the sludge to form the cake. A solid or semi-solid cake is said to be obtained by adding the organic high molecular flocculant to  
10 the sludge and residual water is removed by adding the inorganic treatment agent.

- JP06343999 describes a pre-treatment process for supplying sludge to a belt press type dehydrator. A high molecular weight cationic polymeric coagulant is  
15 added to the sludge to bring about flocculation which then provides a bulky flock structure. This is concentrated by a gravity dehydrator. A high cationicity polymeric coagulant is then added to this concentrated sludge which is then dewatered by belt press.

- 20 JP06344000 describes a process for mechanically dewatering sludge. A high molecular weight cationic polymeric coagulant is added to the sludge to bring about flocculation which then provides a bulky flock structure. This is then concentrated by a gravity dehydrator. A high cationicity polymeric coagulant is then added to this concentrated sludge which is then dewatered in a mechanical  
25 dehydrator.

- EP-A-1035077 describes a process and assembly to dewater sludge, the sludge is fed to a mixing zone and treated with a flocculant. The flocculated  
sludge is removed from the mixing zone, subjected to preliminary dewatering  
30 and then subjected to a second flocculating process in a second mixing zone. The resulting thickened sludge is dewatered within a pressurized assembly to

provide dewatered sludge and clear water is discharged from the secondary mixing zone prior to entry into the pressurise zone.

- 5 It would be desirable to provide an improved process that results in dewatering of suspensions to provide increased cake solids. In particular it would be desirable to provide such a process that involves treatment agents that can be easily and conveniently manufactured and applied.

- 10 According to the present invention we provide a process of dewatering an aqueous suspension comprising dosing the suspension with a flocculating amount of a first flocculant to form a thickened suspension and mixing into the thickened suspension a dewatering amount of a second flocculant and  
15 subjecting the thickened suspension to mechanical dewatering to form a cake, characterised in that the second flocculant comprises a water-soluble or water swellable polymer which is added to the suspension in the form of (i) substantially dry polymer particles or (ii) an aqueous composition comprising dissolved or hydrated polymer having a polymer concentration of at least 1.5% by weight and an IV at least 3 dl/g.

- 20 The invention is applicable to any suitable suspensions in which it is desirable to concentrate suspended solids. This includes waste waters, textile industry effluents, mineral suspensions such as red mud from the Bayer Alumina process or coal tailings, paper mill wastes such as cellulosic sludges. The process is particularly applicable to the dewatering of sewage sludge.

- 25 In the dewatering process the suspension is first thickened following the addition of a first flocculant. This stage involves the initial flocculation and release of free water to produce the thickened suspension. Generally the release of free water may be achieved by free drainage or filtration and it is  
30 common to employ mechanical means such as a belt thickener or rotary drum thickener. Typically addition of the first flocculant would be into the initial bulk

suspension. The flocculant should be added in sufficient quantity to bring about initial flocculation and partial dewatering of the suspension. Preferably the suspension is thickened to produce a semi solid sludge paste. In general this first flocculant will be a polymer added in a conventional manner and at a conventional concentration, for instance 0.1% to 1% by weight, especially 0.2% to 0.5%.

The dewatering process requires mixing a second flocculant into this thickened suspension in which the second flocculant is either in the form of dry polymer particles or an aqueous composition of dissolved or hydrated polymer having a polymer concentration of at least 1.5% by weight. The dry particulate or high concentration aqueous second flocculant can be easily mixed into the thickened suspension and distributed throughout using conventional mixing equipment. Suitable mixing equipment includes, for instance, ribbon type mixers or kneading mixers. Ribbon type mixers consist of helical or spiral mixing blades that sweep across nearly the entire surface of the mixing vessel. Kneading mixers consist of two kneading arms that intermesh as well as form a close tolerance to the mixer wall.

The thickened sludge is then subjected to mechanical dewatering which will release more water to produce a dewatered cake. Typically, this mechanical dewatering will normally involve compression and can for instance be any of belt press, filter press, screw press or centrifuge. When this treated thickened suspension is subjected to mechanical dewatering unexpectedly high cake solids can be achieved.

In one form of the invention the second flocculant is introduced into the thickened suspension in the form of dry polymeric particles. The polymeric particles may have a particle diameter as high as 2000 or 3000 microns or higher or can be as low as 10 or 20 microns or lower, although usually will not be below 50 microns. Generally the particle diameter will be in the range of 50

7

microns to 2000 microns. Preferably, the particles will have a diameter between above 100 and 800 microns, for instance 120 or 150 to 800 microns. More preferably the particles will range between 250 and 750 microns. The particles may also be defined by weight average particle diameter generally this will be  
5 between 50 and 1000 microns, preferably 100 to 800 microns and more preferably between 300 and 700 microns.

In a further embodiment the second flocculant may be introduced in the suspension in the form of a slurry of second flocculant polymer particles in a  
10 liquid. The liquid may be a suitable liquid and that does not adversely interact with either the particles of the second flocculant or the suspension. Suitably the liquid can be a polyethyleneglycol.

The second flocculant may also be introduced into the thickened suspension as  
15 an aqueous composition comprising either dissolved and/or hydrated polymer. The aqueous composition will comprise at least 1.5% by weight polymer, preferably at least 2%. The aqueous composition may comprise as much as 10% or more polymer but generally useful results are obtained when the polymer concentration is between 2% and 5% by weight.

20

The first and second flocculants may be any suitable natural or synthetic polymeric flocculant and typically will be high molecular weight. Natural polymers include for instance cationic starch, anionic starch and chitosan etc. Synthetic polymers include linear, branched and cross-linked polymers of  
25 ethylenically unsaturated monomers. The first flocculant may be the same as the second flocculant or alternatively the two flocculants may be different. Usually the polymer of the first flocculant and second flocculant will be of molecular weight in excess of 500,000, usually at least one million and normally 5 million up to 30 million.

30

The first and second flocculants of the present invention may be cationic, anionic, nonionic or amphoteric in nature. The choice of polymeric flocculant will largely depend upon the substrate. For instance it is common practice to use high molecular weight cationic flocculants to treat aqueous suspensions comprising suspended organic material, for instance sewage sludge. In treating paper-mill waste it is known to use any of cationic, nonionic, anionic or amphoteric flocculants. Flocculation of mineral suspensions is frequently effected by use of anionic flocculants.

10 The polymer may be prepared by polymerisation of a water soluble monomer or water soluble monomer blend. By water soluble we mean that the water soluble monomer or water soluble monomer blend has a solubility in water of at least 5g in 100 ml of water. The polymer may be prepared conveniently by any suitable polymerisation process.

15

When the water soluble polymer is nonionic the polymer may be formed from one or more water soluble ethylenically unsaturated nonionic monomers, for instance acrylamide, methacrylamide, hydroxyethyl acrylate, N-vinylpyrrolidone. Preferably the polymer is formed from acrylamide.

20

When the water soluble polymer is anionic the polymer is formed from one or more ethylenically unsaturated anionic monomers or a blend of one or more anionic monomers with one or more of the nonionic monomers referred to previously. The anionic monomers are for instance acrylic acid, methacrylic acid, maleic acid, crotonic acid, itaconic acid, vinylsulphonic acid, allyl sulphonic acid, 2-acrylamido-2-methylpropane sulphonic acid and salts thereof. A preferred polymer is the copolymer of sodium acrylate with acrylamide.

25 Preferably the water soluble polymer is cationic and is formed from one or more ethylenically unsaturated cationic monomers optionally with one or more of the nonionic monomers referred to herein. The cationic polymer may also be

30

amphoteric provided that there are predominantly more cationic groups than anionic groups. The cationic monomers include dialkylamino alkyl (meth) acrylates, dialkylamino alkyl (meth) acrylamides, including acid addition and quaternary ammonium salts thereof, diallyl dimethyl ammonium chloride.

- 5 Preferred cationic monomers include the methyl chloride quaternary ammonium salts of dimethylamino ethyl acrylate and dimethyl aminoethyl methacrylate. A particularly preferred polymer includes the copolymer of acrylamide with the methyl chloride quaternary ammonium salts of dimethylamino ethyl acrylate.

- 10 The polymers may be linear in that they have been prepared substantially in the absence of branching or cross-linking agent. Alternatively the polymers can be branched or cross-linked, for example as in EP-A-202780.

- Desirably the polymer may be prepared by reverse phase emulsion  
15 polymerisation, optionally followed by dehydration under reduced pressure and temperature and often referred to as azeotropic dehydration to form a dispersion of polymer particles in oil. Alternatively the polymer may be provided in the form of beads by reverse phase suspension polymerisation, or as a powder by aqueous solution polymerisation followed by comminution, drying  
20 and then grinding. The polymers may be produced as beads by suspension polymerisation or as a water-in-oil emulsion or dispersion by water-in-oil emulsion polymerisation, for example according to a process defined by EP-A-150933, EP-A-102760 or EP-A-126528.

- 25 It is particularly preferred that the second flocculant is formed from at least 30% by weight cationic monomer or monomers. Even more preferred are polymers comprising at least 40 or 50% by weight cationic monomer units. It may be desirable to employ cationic polymers having very high cationicities, for instance up to 80 or even 100% cationic monomer units. It is especially preferred when  
30 the cationic second flocculant polymer is selected from the group consisting of cationic polyacrylamides, polymers of dialkyl diallyl ammonium chloride, dialkyl

amino alkyl (meth) -acrylates (or salts thereof) and dialkyl amino alkyl (meth)-acrylamides (or salts thereof).

As stated previously the second flocculant is desirably of relatively high  
5 molecular weight. Normally the second flocculant is particulate and it will be a polymer that exhibits an intrinsic viscosity of at least 0.5 dl/g. Typically the intrinsic viscosity will be at least 3 dl/g, and often it can be as high as 20 or 30 dl/g but preferably will be between 4 and 10 dl/g. When introduced as an aqueous composition the second flocculant will be at least 3  
10 dl/g, and can also be as high as 20 or 30 dl/g and also preferably will be between 4 and 10 dl/g.

Intrinsic viscosity of polymers may be determined by preparing an aqueous solution of the polymer (0.5-1% w/w) based on the active content of the  
15 polymer. 2 g of this 0.5-1% polymer solution is diluted to 100 ml in a volumetric flask with 50 ml of 2M sodium chloride solution that is buffered to pH 7.0 (using 1.56 g sodium dihydrogen phosphate and 32.26 g disodium hydrogen phosphate per litre of deionised water) and the whole is diluted to the 100 ml mark with deionised water. The intrinsic viscosity of the polymers are measured  
20 using a Number 1 suspended level viscometer at 25°C in 1M buffered salt solution.

One particularly useful cationic polymer type for use as second flocculant includes 50 to 100% by weight methyl chloride quaternary ammonium salt of  
25 dimethyl amino ethyl (meth) acrylate and 0 to 50 % by weight acrylamide of intrinsic viscosity between 4 and 10 dl/g. Preferably the cationic polymer comprises at least 80% methyl chloride quaternary ammonium salt of dimethyl amino ethyl (meth) acrylate.

Other suitable polymeric second flocculants include polyvinyl amidine and polyvinyl amines of intrinsic viscosity greater than 1 dl/g, preferably greater than 2 dl/g.

- 5 Another particularly suitable category of second flocculants are Mannich addition polyacrylamides. Ideally such polymers will exhibit an intrinsic viscosity greater than 1 dl/g and quite often can be at least 4 dl/g, for instance at least 7 or 8 dl/g. Such polymers may be made by reacting formaldehyde / amine adducts with polyacrylamide. The amine may for instance be dimethylamine or other secondary amines. Preferably the Mannich addition polyacrylamides are quaternised salts and these could be prepared by reacting the free base Mannich with a suitable quaternising agent such as methyl chloride or dimethyl sulfate.

- 10 15 A further suitable polymer as the second flocculant includes poly dimethyl diallyl ammonium chloride of intrinsic viscosity greater than 0.5 dl/g, preferably at least 1 dl/g.

- 20 Effective dewatering can be obtained when these polymers are added as a second flocculant to the thickened suspension.

- The dose of aqueous composition depends on the substrate and usually this will be a conventional amount. Typically for sewage sludge treatment the dose of the aqueous composition (second flocculant) found to be an effective dewatering amount is often at least 50 mg active polymer per litre of suspension. Usually the amount would be higher for instance up to 400 mg per litre. Preferred doses are between 60 and 300 mg per litre. The quantity of first flocculant used will usually be at least 50 mg active polymer per litre of suspension and can be as high as 500 or 600 mg per litre. Preferred doses would be between 100 and 400 mg per litre.

Various polymers may be used as the first flocculant in order to obtain a suitably thickened suspension for treatment with the second flocculant. Preferably the first flocculant is a cationic organic polymer. This is particularly true when the suspension is a sewage sludge. Preferred cationic polymers include polymers  
5 selected from the group consisting of acrylamide polymers, polyvinyl amidine, polyvinyl amine, poly dimethyl diallyl ammonium chloride, poly amines, polyethyleneimines, mannich polyacrylamides and quaternised mannich polyacrylamides.

10 The following example is an illustration of the invention.

ExampleDewatering of aqueous suspensions using a two-stage addition of organic polymer flocculant5 Polymers

Polymer A is a linear, high molecular weight, cationic acrylamide based polymer of intrinsic viscosity 12 dl/g in dehydrated emulsion (liquid dispersion product) form. Polymer B is a linear, cationic quaternised dimethyl amino ethyl methacrylate based homopolymer in bead form of intrinsic viscosity 5 dl/g.

10

Unless otherwise stated intrinsic viscosity is measured using a Number 1 suspended level viscometer, in 1M sodium chloride buffered to pH 7 in accordance with the information given in the description.

15 Test substrate

Dewatering tests were conducted on a sample of a digested, mixed primary/activated sludge. The sample had a dry solids content of 3.28%.

Experimental procedure20 (A) Two-stage addition of polymer

25 i) Polymer A was first dissolved in deionised water to give a homogeneous 1% w/v solution and further diluted to 0.25%w/v prior to use. Polymer B was dissolved in deionised water to give three homogeneous solutions of 1%w/v, 5%w/v and 20%w/v. The 1%w/v solution was further diluted with deionised water to 0.25%w/v prior to use.

30 ii) 250 ml of a digested mixed primary/activated sludge was placed in a 1 litre plastic beaker (120cm diameter by 120cm tall). A standard laboratory stirrer was secured over the beaker with the stirrer shaft located through

14

a hole in the centre of the beaker lid. The stirrer is a four bladed, flat crosshead type (each paddle is 25cm width by 1.1cm).

5           iii) the appropriate volume of a 0.25% solution of Polymer A was added to the sludge using a syringe and the lid secured to the beaker. The sludge was flocculated by stirring at 1500rpm for 10s. The flocculated sludge was poured into a filtration cell, which had a filter membrane comprising an 8cm diameter belt-press filter cloth, and the filtrate collected in a measuring cylinder.

10           iv) after 30s drainage the thickened sludge retained on the filter cloth was subjected to a 'furrowing' technique, whereby a spatula was slowly drawn across the sludge in several directions to encourage release of more water. Furrowing was carried out for 30s. The volume of filtrate was  
15           noted.

          v) the thickened sludge was transferred to a 250ml beaker. Polymer B was then added into the thickened sludge. Polymer B solutions, ie 0.25%, 5% and 20%w/v, were applied using a syringe, whilst dry Polymer  
20           B was simply sprinkled onto the top of the thickened sludge. To mix in the polymer the treated thickened sludge was stirred by hand for 45s with a spatula, using a slow, circular folding action.

          vi) the polymer treated thickened sludge was then transferred to a piston-  
25           press apparatus and subjected to a compression dewatering stage. Dewatering was commenced using a pressure of 20psi for 2 minutes, followed by increases of 10psi at one minute intervals for a further 3 minutes to a maximum of 60psi. Pressure was maintained at 60psi for a further 5 minutes, giving a total compression dewatering time of  
30           10minutes. Cake solids content was determined by heating at 110°C overnight.

(B) Control – conventional first-stage addition of dilute polymer(s), including mixing of the thickened sludge.

5           The procedure was exactly the same as that described in Section (A) except:

10           In sub-section iii) the appropriate volume of a 0.25%w/v solution of polymer B was added simultaneously with the 0.25% solution of Polymer A.

15           In sub section v) the addition of polymer B was omitted; nevertheless the thickened sludge was stirred by hand for 45s with a spatula, using a slow, circular folding action.

(C) Control - conventional first-stage addition of dilute polymer(s) excluding mixing of the thickened sludge.

20           The procedure was exactly the same as that described in Section (A) except:

25           In section iii) the appropriate volume of a 0.25%w/v solution of polymer B was added simultaneously with the 0.25% solution of Polymer A.

25           Section v) was omitted

Results

The results of test (A) are given in Table 1

30           The results of tests (B) and (C) are given in Table 2

Table 1 – results of two-stage addition of polymer

| Polymer A<br>Dose (mg/l) | Filtrate<br>Volume (ml) | Polymer B   |                         | Cake<br>solids(%) |
|--------------------------|-------------------------|-------------|-------------------------|-------------------|
|                          |                         | Dose (mg/l) | Solution strength (w/v) |                   |
| 200                      | -                       | 75          | 0.25%                   | 20.40             |
| 200                      | 168                     | 100         | 0.25%                   | 20.86             |
| 200                      | -                       | 150         | 0.25%                   | 21.88             |
| 200                      | 164                     | 75          | 5.0%                    | 19.62             |
| 200                      | -                       | 100         | 5.0%                    | 20.72             |
| 200                      | -                       | 150         | 5.0%                    | 22.27             |
| 200                      | 170                     | 75          | 20%                     | 18.52             |
| 200                      | -                       | 100         | 20%                     | 19.72             |
| 200                      | -                       | 150         | 20%                     | 21.77             |
| 200                      | 168                     | 75          | Dry product<500 $\mu$   | 18.65             |
| 200                      | -                       | 100         | Dry product<500 $\mu$   | 20.30             |
| 200                      | -                       | 150         | Dry product<500 $\mu$   | 22.21             |

Table 2 – results of first stage addition of conventional dilute solutions

5

| Polymer A<br>Dose (mg/l) | Filtrate<br>Volume (ml) | Polymer B  |                        | Cake<br>solids(%) |
|--------------------------|-------------------------|------------|------------------------|-------------------|
|                          |                         | Dose(mg/l) | Solution strength(w/v) |                   |
| 200                      | 170                     | 75         | 0.25%                  | 14.60             |
| 200                      | 174                     | 100        | 0.25%                  | 15.15             |
| 200                      | 180                     | 150        | 0.25%                  | 15.81             |
| 200                      | -                       | 75         | 0.25%                  | 16.78*            |
| 200                      | 176                     | 100        | 0.25%                  | 16.39*            |
| 200                      | 178                     | 150        | 0.25%                  | 17.27*            |

\* Omission of second stage mixing of thickened sludge

The results in Tables 1 and 2 demonstrate that drier cake solids are produced using a two-stage addition of polymer.

17

The results in Table 1 show that high strength polymer solution (5% and 20%) and substantially dry polymer, are as effective as conventional polymer solution strength (0.25%) in giving drier cake solids.

5

The results in Table 2 also show that, with conventional treatment, additional mixing of the thickened sludge (Set1) has an adverse effect on cake solids compared to no additional mixing (Set 2).

10

15

20

25

Claims

1. A process of dewatering an aqueous suspension comprising dosing the suspension with a flocculating amount of a first flocculant to form a thickened suspension and mixing into the thickened suspension a dewatering amount of a second flocculant and subjecting the thickened suspension to mechanical dewatering to form a cake,  
characterised in that the second flocculant comprises a water-soluble or water swellable polymer that is mixed into the suspension in the form of (i) substantially dry polymer particles or (ii) an aqueous composition comprising dissolved or hydrated polymer having a polymer concentration of at least 1.5% by weight and having a intrinsic viscosity of at least 3 dl/g. .
2. A process according to claim 1 in which the aqueous suspension is sewage sludge.
3. A process according to claim 1 or claim 2 in which the mechanical dewatering employs an apparatus selected from the group consisting of belt press, filter press, screw press and centrifuge.
4. A process according to any of claims 1 to 3 in which the second flocculant is in the form of an aqueous composition comprising dissolved or hydrated polymer having a polymer concentration between 2 and 5% by weight.
5. A process according to any of claims 1 to 4 in which the second flocculant is a cationic polymer.
6. A process according to any of claims 1 to 5 in which the second flocculant is formed from at least 30% by weight cationic monomer or monomers.
7. A process according to any of claims 1 to 6 in which the second flocculant is selected from the group consisting of cationic polyacrylamides, polymers of dialkyl diallyl ammonium chloride, dialkyl amino alkyl (meth) - acrylates (or salts thereof) and dialkyl amino alkyl (meth)-acrylamides (or salts thereof).

8. A process according to any of claims 1 to 7 in which the second flocculant has an intrinsic viscosity of at least 0.5 dl/g, preferably 4 to 10 dl/g.

9. A process according to any of claims 1 to 8 in which the second flocculant is selected from the group consisting of,

5 i) a polymer formed from 50 to 100% by weight methyl chloride quaternary ammonium salt of dimethyl amino ethyl (meth) acrylate and 0 to 50% by weight acrylamide of intrinsic viscosity between 4 and 10 dl/g,

ii) polyvinyl amidine and polyvinyl amines of intrinsic viscosity greater than 1 dl/g,

10 iii) quaternised salts of Mannich addition polyacrylamides of intrinsic viscosity greater than 1 dl/g, and

iv) poly dimethyl diallyl ammonium chloride of intrinsic viscosity greater than 0.5 dl/g.

15 10. A process according to any of claims 1 to 9 in which the first flocculant is a cationic organic polymer.

11. A process according to claim 10 in which the polymer is selected from the group consisting of acrylamide polymers, polyvinyl amidine, polyvinyl amine, poly dimethyl diallyl ammonium chloride, poly amines, polyethyleneamines, mannich polyacrylamides and quaternised mannich polyacrylamides.

20 12. A process according to any of claims 1 to 11 in which the second flocculant is introduced into the suspension in form of a slurry in a liquid.

13. A process according to claim 12 in which the liquid is polyethylene glycol.

AbstractDewatering Process

- A process of dewatering an aqueous suspension comprising dosing the suspension with a flocculating amount of a first flocculant to form a thickened suspension and mixing into the thickened suspension a dewatering amount of a
- 5 second flocculant and subjecting the thickened suspension to mechanical dewatering to form a cake,
- characterised in that the second flocculant comprises a water-soluble or water swellable polymer that is mixed into the suspension in the form of (i)
- 10 substantially dry polymer particles or (ii) an aqueous composition comprising dissolved or hydrated polymer having a polymer concentration of at least 1.5% by weight and having an intrinsic viscosity of at least 3 dl/g. .



